



## DECLARATION OF PERFORMANCE No. 35/1

1. **Birch Plywood Type FSF with the thickness < 9 mm (FSF < 9)**
2. For internal use in humid conditions (uncoated) – EN 636-2 NS – and for external use (coated and with sealed edges) ) – EN 636-3 NS – as non-structural components – EN 13986 : 2004+A1:2015 (4.5, 4.6)
3. Manufacturer: **LLC “SVEZA Uralskiy”**  
1a Moskovskaya str., Uralskiy, Nytva District, Perm Region 617005, RUSSIA
4. System of assessment and verification of consistency of performance of the construction product as set out in Annex V of the Regulation (EU) No 305/2011: EN 13986:2004+A1:2015 System 4
5. Declared performance:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonized technical specification</i>
Bonding quality (Moisure resistance)	Class 3	EN 636 : 2012, EN 314-2:1993
Release of formaldehyde	E1	EN 636 : 2012, Table 3
Reaction to fire	Class E	EN 13986, Table 8
Water vapour permeability (by mean density of 691 kg/m <sup>3</sup> )	Vapour resistance factor: 89 μ (wet cup); 219 μ (dry cup)	EN 12524; EN 13986, Table 9
Airborne sound insulation	NPD	
Sound absorption (not valid for external use)	0.10 (250 Hz to 500 Hz) 0.30 (1 000 Hz to 2 000 Hz)	EN 13986, Table 10
Thermal conductivity (by mean density of 691 kg/m <sup>3</sup> )	0.17	EN 13986, Table 11
Biological durability	NPD	EN 13986, 5.17
Content of pentachlorophenol	< 5 ppm	EN 13986, 5.18

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Denis L. Maltsev  
Director of Branch „Uralskiy“  
of LLC „SVEZA“

Uralskiy, August 25<sup>th</sup>, 2017