



DECLARATION OF PERFORMANCE No. 45/7

- Birch Plywood SVEZA Parquet Type FSF with the thickness < 9 mm (SVEZA 1. Parquet < 9)
- 2. For internal use in humid conditions (uncoated) – EN 636-2 NS – as non-structural components – EN 13986 : 2004+A1:2015 (4.5)
- JSC "SVEZA Verhnaya Sinyachiha" 3. Manufacturer:

1 Kedrovaya str., Verhnaya Sinyachiha, Alapaevsk District, Sverdlovsk

Region 624691 RUSSIA

- System of assessment and verification of consistency of performance of the construction 4. product as set out in Annex V of the Regulation (EU) No 305/2011: EN 13986:2004+A1:2015 System 4
- 5. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Bonding quality (Moisure resistance)	Class 3	EN 636 : 2012, EN 314-2:1993
Release of formaldehyde	E1	EN 636 : 2012, Table 3
Reaction to fire	Class E	EN 13986, Table 8
Water vapour permeability (by mean density of 641 kg/m³)	Vapour resistance factor: 84 μ (wet cup); 214 μ (dry cup)	EN 12524; EN 13986, Table 9
Airborne sound insulation	NPD	
Sound absorption (not valid for external use)	0.10 (250 Hz to 500 Hz) 0.30 (1 000 Hz to 2 000 Hz)	EN 13986, Table 10
Thermal conductivity (by mean density of 641 kg/m³)	0.16	EN 13986, Table 11
Biological durability	NPD	EN 13986, 5.17
Content of pentachlorophenol	< 5 ppm	EN 13986, 5.18

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Ilya V. Radchenko

Director of Branch «Verhnaya

Sinyachilia of LLC SVEZA

The state of the s

Verhnaya Sinyachiha, August 28th, 2017